



METZNER KL-BV

CONVENIENT TABLETOP MODEL WITH EXCELLENT PRICE-PERFORMANCE RATION

The hose specialist with unique precision and working speed for very thin, tensile-elastic and pressure-sensitive materials.

- Long belt feed in conjunction with the centrally adjustable contact pressure ensures slip-free material transport
- Gentle on the material
- Blade cut" as standard
- Outstanding cutting quality at up to 400 cuts per minute



Performance Data

Material dimensions Width max.	Ø 12 mm or Ø 18 mm
Material dimensions Height max.	Ø 12 mm or Ø 18 mm
Length interval	0,1 mm
Typical repeatability ¹⁾	± 0,2%

Technical Data

Electrical connection	230 V, 50/60 Hz, 6 A
Compressed air connection	6 bar
Dimensions (LxWxH)	400 x 370 x 650 mm
Weight	65 kg

Equipment

Feed rate m/min	60
Cuttin capacity/min ²⁾	330
Control ³⁾	PLC
Display	5.7" Farbe (Touch)
Engine	3~Stepper motor.

1) depending on material; minimum tolerance ± 0.5 mm | 2) for 5 mm cutting length | 3) PLC = PLC control with CoDeSys programming | 4) 25 mm for ST-OB Red with 30° knife, 20 mm for ST-OB with 45° knife | Subject to technical changes.