

METZNER AM 1000

AUTOMATIC CABLE ASSEMBLY MACHINE



For cutting and stripping cables, strands and wires up to 9 mm diameter and 10 mm² cable cross section



METZNER AM 1000

The Metzner AM 1000 is a sensation among the tabletop units. The automatic cutting and stripping machine processes cables, strands and wires up to 9 mm diameter and 6 mm² cable cross-section with a special cutting and pull-off force (optionally 10 mm²; depending on material). The presettings are conveniently made via the modern 12" touch panel, where the operator can define all processes. Another special feature is the tool-free change of wear parts and guides. This means that the AM 1000 can be changed over in just one minute. With the extensive interface preparation, the machine can be optimally expanded with peripheral devices and adapts to all customer requirements. The compact design with retractable touchscreen and the low weight of only 28 kg also offers particular convenience. This makes the AM 1000 especially easy to transport.



INTERFACE FOR PERIPHERALS





TOOL-FREE CHANGE

- Changeover of guide rollers, tube and knife in less than 1 min

SUPERIOR PERFORMANCE SPECTRUM

Ready for bigger tasks - 66% more power in terms of diameter and cross-section



- More power
- More diameter
- More cross section
- Versatile in use

1) depending on material



ALL TECHNICAL DETAILS AT A GLANCE

| Functions/Programs | AM 1000 |
|---------------------------------|------------------------|
| Cutting to length | ✓ |
| Stripping with full pull-off | ✓ |
| Stripping with partial pull-off | ✓ |
| Stripping in multiple steps | ✓ |
| Slitting | - |
| Multiple stripping | - |
| Flat cables | optional ≤ 10 mm Width |
| BOM processing | ✓ |
| Material end detection | - |
| Cable length correction | ✓ |
| Recipe data management | ✓ |
| Length measurement system | optional |

| Machine Parameters | AM 1000 |
|---|---|
| Transport unit belt/roll | Roll |
| Networking / MES interface (Industry 4.0) | optional |
| Remote maintenance | ✓ PC integrated |
| Cable cross section stranded conductor | 6 mm ² |
| max. outer diameter | 10 mm |
| Cable length | 35 mm - 99.999 mm |
| max. Cable transport speed | 220 m/min |
| max. Stripping length full stripping | Cable start: 40-120 mm Cable end: 0-30 mm |
| USB/Ethernet | ✓ |
| Electrical connection | 230V; 50 Hz |
| Pneumatic connection | 6bar |
| Dimensions in mm | 390x600x370 (PC on top 540) |
| Weight | 28 kg |
| Rotary cutting unit | - |
| Screen | 12" touchscreen, tiltable |