METZNER CCM 2

UNIVERSALLY APPLICABLE FOR STEEL-REINFORCED PROFILES AND HOSES



FEATURES

- Variable-speed saw motors in various speed ranges (2,000–3,000 rpm or 4,000–10,000 rpm)
- Wide selection of specialized circular saw blades and cutting discs. This allows you to tailor the machine precisely to the physical properties of your material

AVAILABLE CUTTING TECHNOLOGY CCM 2



CIRCULAR KNIFE CUT

TECHNICAL DETAILS AT A GLANCE

Performance Data	**Metzner CCM 2**
Application	Dry cutting of steel-reinforced materials
Max. material width[1]	65 mm[1]
Max. material height[1]	30 mm[1]
	[1]larger product dimensions available on request
Length interval	0.1 mm
Typical repetition accuracy	± (1 mm + 0.2 % L)
Max. feed rate	60 m / min
Cutting performance / min[2]	up to 100 cuts / min[2]
Speed / min	up to 2000 – 3000 / 4000 – 10 000 rpm
Technical Data	**Metzner CCM 2**
Dimensions (L x W x H)	2060 x 750 x 1680 mm
Electrical connection	3 ~ 400 V | 50 / 60 Hz | 16 A
Weight	400 kg
Control system	Siemens
Display	7" color (touchscreen)
Consumption values kVA | bar	P: 1.0 kVA | approx. 120 l / min
Noise level (idle)	< 75 dB (A)
Features	**Metzner CCM 2**
Cooling water circuit	–
Minimum quantity lubrication	●
Gap detection	o
Additional cutting tool	o
Integrated interfaces for peripheral devices	●
E-Service module	o

● = standard, o = optional, – = not available | [2] at a product length of 5 mm and depending on the cutting method | Technical changes reserved.

Metzner Maschinenbau GmbH | Messerschmittstraße 30 | D-89231 Neu-Ulm | +49 (0) 731 40 199 0 | info@metzner.com | **www.metzner.com**